## **VPOS Touch**

### All-in-one Card Reader and Telemetry Terminal






Plug & Play Installation



Multi-Lingual Voice and Text Ineraction





#### Accepts all types of payment methods

- Debit and Credit cards
- Mobile and NFC Payments
- Swipe, contact and contactless
- Prepaid cards and closed environment solutions
- QR codes















































repaid cards

#### The Nayax Difference:

A Complete Solution for Your Business



Advanced Payment Technology



Integrated POS




Actionable Management Suite



Marketing & Loyalty Solutions





# A complete payment solution for unattended automated machine operators.

Benefit from easy installation, clearance, monitoring and management.

Installation Environment				
Operating Temperature	-20°C to +55°C / -4°F to +131°F			
Storage Temperature	-30°C to +85°C / -22°F to +185°F			
Humidity	ity 25% to 95% (non-condensing)			
Dust & Water Resistance	IP 55			
Flammability	UL-94 V0			
Safety	CE, FCC, RoHS			

Physical Dimension	s
Height	105 mm / 4.1 inch
Width	84.7 mm / 3.3 inch
Depth	45.3 mm / 1.78 inch
Weight	230 grams / 8.1 ounces

Interface & Management		
Display	Color Touch LCD screen 2.4 inch, 320 x 240 Pixels + 4 LEDs + 6 touch buttons	
Architecture	ARM Technology – 2 x Cortex, 32 bit, 180/216MHz	
Audio	Speaker + Buzzer	
Localization	Multi language support - LCD text & voice audio instructions	
Security	Support DES, 3DES, AES, RSA, ECC, SHA1 algorithms, Random Number Generator	
Power Supply	12-42V DC, 12-24V AC; 5 Watts. Recommended External Power Supply: 24V DC / 2Amp	
Anti-vandal	Internal shock/tilt detector, anti-vandal Dragontrail glass	
Power Loss Protection	Super Caps with safe shutdown mechanism	
External Interface	Ethernet, 2 X RS232 (RS232 or TTL level through SW), External reader, 1 X door open sensor, 1 X temperature sensor	
Pulse Input/Output	6 pulse input/output interfaces + 1 Inhibit input	
Communication	4G/Ethernet/NFC	
Vending Machine Protocols	MDB / DEX / DDCMP / Pulse / VCCS / ccTalk / JVMA	

Payment Support				
Contact	EMV Level 1, EMV Level 2			
Magnetic Stripe	ISO 7811 and JIS I Tracks 1,2,3 JIS I		Contactless	Level 2: Visa payWave, MasterCard PayPass, Interac Flash,UnionPay qPBOC, AMEX ExpressPay, JCBJ/Speedy, FeliCa, Interac Flash, , Discover D-PAS, CUP QuickPass,
Other Cards Supported	13.56 MHz : NFC, MIFARE, ISO 14443 Type A and B, ISO 15693, SONY® FeliCa			



Let Nayax help your business maximize your profits!

